Sanitized Copy Approved for Release 2010/05/20: CIA-RDP67B00511R000100240005-0

Jule Rist

COPT

COPY

6 October 1959

MESSORANDUM FOR: Mr. W. R. Lampehire, SRS/OPD-DD/P

SUBJECT:

Telemetry Receiver for Discussion at the New

Techniques Committee

1. The following excerpt is from the magazine "Missiles and Rockets", 24 August 1959:

"Predetection recording -- One of the most significant advancements in telemetry reception is that of predetection recording. This technique, first used in the reception of radar signals from Venus by Lincoln Lab's Milistone automa. offers great premise in higher reliability of telemetered signals. Receiver input is picked off just ahead of the detection stage, tape recorded then later demodulated.

"The advantage here is in the possibility of applying advanced demodulation techniques to periods in which data are lost due to poor signal - to - noise ratio of interference. Future improvements in this technique are expected to significantly advance long-range telemetry.

"Radiation, Inc., has designed and built models of a 2200 mc 'state-of-the-art' receiver which provide this feature. Production of commercial medels is centemplated."

2. This type of receiver could possibly be used either on the ground or in an airborne platform and will be investigated for possible use as an ELINT telemetry receiver.

25X1			
ELINT	Staff	Officer	

25 YEAR RE-REVIEW